



Specifications Ledvance LED Downlight Comfort UGR19 Aluminium 13W/10W/7W 1430lm/1100lm/770lm 95D - 930-940 CCT | Cutout 100mm - IP44 - Best Colour Rendering

[View Product](#)

General Information

| | |
|--------------------------|---------------------------------------|
| SKU | 254997 |
| EAN | 4099854490903 |
| Brand | Ledvance |
| Manufacturer Name | DL CMFT D100 P 13W MS 940 U19 WT LEDV |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 1x18 |
| Wattage | 13 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 930 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 90-99 |
| Colour of Light | White |
| Light colour options | Single Color |

| | |
|--------------------------|--------------------------------|
| Beam Angle (degree) | 55 |
| Luminous Flux (Lumen) | 1430 |
| Luminous Efficacy (lm/W) | 110 |
| Power factor | >0.90 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 100 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector] |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 65 |
| Diameter (mm) | 116 |

Sensor Information

Why Any-lamp?

Type of sensor **No Sensor**

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 **Up to 7 years warranty**  **Easy** return process