



**Specifications Noxion LED Panel Delta Pro V2.0 30W 4110lm - 865 Daylight | 60x60cm - UGR <19 - Dali Dimmable - Philips Xitanium Driver**

[View Product](#)

## General Information

|                          |                                                                               |
|--------------------------|-------------------------------------------------------------------------------|
| SKU                      | 238285                                                                        |
| EAN                      | 8719157012614                                                                 |
| Brand                    | Noxion                                                                        |
| Manufacturer Name        | Noxion LED Panel Delta Pro UGR<19 V2.0 Xitanium DALI 30W 4110lm 6500K 600x600 |
| Any Lamp all-in warranty | 6 Years                                                                       |
| Average Lifetime (h)     | 50000                                                                         |
| Series                   | Delta Pro                                                                     |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 30                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 865 Daylight       |
| Colour temperature (Kelvin) | 6500 Daylight      |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 4110               |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 125               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation


 Up to **7 years warranty**


**Easy** return process